



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

GRAFFITI REMOVER SAC

Product Number: 3071; 3171

Spartan Chemical Company, Inc.

1110 Spartan Drive

Maumee OH 43537

Product Division:

Janitorial

Product/Technical **1-(800)-537-8990**

Information:

Medical Emergency: **1-(888)-314-6171 (24 hours)**

Chemical Leak/Spill: **CHEMTREC 1-(800) 424-9300 (24**

Emergency: hours)

Shipping Description:	Cleaning compounds, liquid, n.o.s.		
NFPA Ratings:		HMIS Ratings:	
Health:	2 - Moderate	Health:	2 - Moderate
Fire:	2 - Moderate	Fire:	2 - Moderate
Reactivity:	0 - Minimal	Reactivity:	0 - Minimal
		Pers. Prot. Equip.:	See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S.

Environmental Protection Agency.

Chemical Name(s)	% W	CAS Registry No.	Table Z- 1 - A			NTP, IARC or OSHA Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
Petroleum distillate	25-35	64742-47-8	1200 (Exxon)	Not Established	Not Established	No
Soybean oil methyl esters	25-35	67784-80-9	Not Established	Not Established	Not Established	No
Ethyl lactate	25-35	97-64-3	Not Established	Not Established	Not Established	No
Alcohol ethoxylate	5-10	34398-01-1	Not Established	Not Established	Not Established	No
1-undecanol	1-5	112-42-5	Not Established	Not Established	Not Established	No

▼ **SECTION III: PHYSICAL DATA**

Boiling Point:	>300 °F	Vapor Pressure:	Unknown
Vapor Density (AIR = 1):	Unknown	Solubility in Water:	Emulsifiable
pH:	NA	Specific Gravity (H ₂ O=1):	0.834
Evaporation Rate (but.ace.=1):	<1	Percent Solid by Weight:	10-15
Physical State:	Liquid		
Appearance & Odor:		Translucent yellow, bland odor	

▼ **SECTION IV: FIRE & EXPLOSIVE HAZARD DATA**

Flash Point:	147°F	Method Used:	ASTM-D56
Flammable Limits:	Not Established	Flame Extension:	N/A
Extinguishing Media:	Water, carbon dioxide or dry chemical.		
Special Fire Fighting Procedures:	Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.		
Unusual Fire & Explosive Hazards:	Combustible liquid and vapor. Keep away from heat, sparks or flame. Combustion products are toxic. Rags; towels or mops soaked with this product are subject to spontaneous combustion if not handled properly.		

▼ **SECTION V: HEALTH HAZARD DATA**

Threshold Limit Value:	Not Established	Primary Routes of Entry:	Inhalation, Skin Contact, Eyes & Oral
Effects of Overexposure-Conditions to Avoid:	<p>Harmful or fatal if swallowed: Symptoms include pain, nausea, vomiting and diarrhea. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury.</p> <p>Causes eye irritation: Symptoms may include pain, redness and swelling of the conjunctiva.</p> <p>Causes skin irritation: Symptoms may include redness, pain and swelling.</p> <p>Breathing product vapors or mist may cause respiratory irritation: Symptoms may include nasal discomfort and coughing.</p> <p>Avoid contact with eyes, skin and clothing. Avoid breathing product vapors or mists. Do not swallow. Use with adequate ventilation. Wash thoroughly after handling.</p>		
Conditions Aggravated by Use:	Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and dermatitis.		

Emergency & First Aid Procedures:

Eyes:	Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Remove contaminated clothing. Flush skin with water for at least 15 minutes. Get medical attention if irritation persists. Wash contaminated clothing before reuse.
Ingestion:	Call physician immediately for treatment advice. Do not induce vomiting. Do not give anything by mouth to an unconscious person.
Inhalation:	Move person to fresh air. Get medical attention if irritation persists.

▼ **SECTION VI: REACTIVITY DATA**

Stability:	Stable	Incompatible Materials:	Strong acids and oxidizing agents
Hazardous Decomposition Products:	Carbon dioxide, carbon monoxide	Hazardous Polymerization:	Will Not Occur

▼ **SECTION VII: SPILL OR LEAK PROCEDURES**

Steps to be Taken in Case Material is Released or Spilled:	Dike and contain spill with inert material (sand, earth, commercial absorbent, etc.) and transfer to containers for disposal. Keep spill out of storm sewers and waterways.
Waste Disposal Method:	Dispose of in compliance with all federal, state and local laws and regulations.

▼ **SECTION VIII: SPECIAL PROTECTION INFORMATION**

Respiratory Protection:	Not normally required when good general ventilation is provided. However if exposure limits are exceeded (see Section II) or if respiratory irritation occurs, the use of a NIOSH approved respirator suitable for the use-conditions and chemicals listed in Section II should be considered.
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Nitrile, neoprene or other impervious gloves are recommended.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
Other Protective Equipment:	See 29 CFR 1910.132-138 for further guidance.

▼ **SECTION IX: SPECIAL PRECAUTIONS**

Precautions; Handling & Storing:	Combustible liquid and vapors. Flash Point 147°F . Keep container tightly closed. Store in a cool, dry area. Do not freeze. Do not store above 125°F. Product will expand and may cause container to swell and possibly rupture. In case of container expansion, carefully vent container. All handling equipment should be electrically grounded. Do not mix with other chemicals.
Other Precautions:	Rags; towels or mops soaked with this product are subject to spontaneous combustion if not handled properly. Thoroughly rinse these materials with water to remove product before disposal or discard in special containers designed for this purpose. Keep out of reach of children.

© SCC 02/20/2006 Name: Ronald T. Cook Title: Manager, Regulatory Affairs
GRAFFITI REMOVER SAC Effective 02/20/2006 Supercedes: 11/30/2005
 Date:
 Ref: 29 CFR 1910.1200 Changes: Correct Section II
 (OSHA)

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual

conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.