MATERIAL SAFETY DATA SHEET

	1. Product and Company Identification	
Product number	050	
Product name	Sunbelt Clear View Foaming Glass Cleaner	
Effective date	20-Jul-2007	
Manufacturer information	Sunbelt Laboratories P.O. Box 1563 Stafford, TX 77497 United States	
Manufacturer phone	General Assistance 1-800-324-4413	
Emergency telephone US	866-836-8855	
Emergency telephone outside US	952-852-4646	
Supersedes date	20-Jul-2007	
	2. Hazards Identification	
Emergency overview	CONTENTS UNDER PRESSURE.	
	Aerosol. Pressurized container may explode when exposed to heat or flame. May be ignited by heat, sparks or flames. Prolonged exposure may cause chronic effects.	
SHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Commu		
Potential health effects		
Eyes	Health injuries are not known or expected under normal use.	
Skin	This product may be harmful if it is absorbed through the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).	
Inhalation	Intentional misuse by concentrating and inhaling the product can be harmful or fatal.	
Ingestion	Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.	
Target organs	Kidney.	
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.	
	Blood. Central nervous system. Liver. Respiratory system.	
Chronic effects	Unconsciousness. Liver injury may occur. Kidney injury may occur.	
Signs and symptoms	Cyanosis. Liver enlargement. Jaundice. Defatting of the skin. Irritation.	

CAS # 111-76-2	Percent 3 - 5
111-76-2	3 - 5
	7 - 7
64-17-5	3 - 5
74-98-6	3 - 5
106-97-8	3 - 5
	74-98-6

4. First Aid Measures

First aid procedures	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.
Skin contact	Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.
Inhalation	Call a physician if symptoms develop or persist.

Ingestion	Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
Notes to physician	Symptoms may be delayed.
General advice	If you feel unwell, seek medical advice (show the label where possible).

5.	Fire	Fighting	Measures	
----	------	----------	----------	--

e Fires: Water spray, fog or regular foam. I Fires: Dry chemical, CO2, water spray or regular foam. ot use a solid water stream as it may scatter and spread fire. full protective clothing, including helmet, self-contained positive pressure or sure demand breathing apparatus, protective clothing and face mask. Containers Id be cooled with water to prevent vapor pressure build up. Do not scatter spilled
I Fires: Dry chemical, CO2, water spray or regular foam. ot use a solid water stream as it may scatter and spread fire. full protective clothing, including helmet, self-contained positive pressure or sure demand breathing apparatus, protective clothing and face mask. Containers
ot use a solid water stream as it may scatter and spread fire. full protective clothing, including helmet, self-contained positive pressure or sure demand breathing apparatus, protective clothing and face mask. Containers
full protective clothing, including helmet, self-contained positive pressure or sure demand breathing apparatus, protective clothing and face mask. Containers
sure demand breathing apparatus, protective clothing and face mask. Containers
sure demand breathing apparatus, protective clothing and face mask. Containers
rial with high pressure water streams.
. Accidental Release Measures
ot touch damaged containers or spilled material unless wearing appropriate octive clothing. Keep unnecessary personnel away.
nate all ignition sources (no smoking, flares, sparks, or flames in immediate area). leak if you can do so without risk. Move the cylinder to a safe and open area if the is irreparable.
l Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated ce thoroughly.
7. Handling and Storage
surized container: Do not pierce or burn, even after use. Do not handle or store near ben flame, heat or other sources of ignition. Do not use if spray button is missing or tive. Use only with adequate ventilation. Do not get this material in contact with Do not get this material in contact with skin. Avoid prolonged exposure.
1 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH				
Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
OSHA				
Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye / face protection

Not normally needed.

Skin protection	Protective gloves.		
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.		
General hygeine considerations	When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice.		
	9. Physical & Chemical Properties		
Appearance	Compressed liquefied gas.		
Color	Colorless.		
Odor	Butyl		
Physical state	Liquid.		
Form	Aerosol.		
Flammability (HOC)	3.83 kJ/g estimated		
Flash back	No		
Pressure	65 - 75 psig @ 70F		

pH	9.5 - 10.5
	10. Chemical Stability & Reactivity Information
Chemical stability	Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known.
Hazardous decomposition	May include exides of nitrogen

Completely

0.957 estimated

-76 °F (-60 °C) estimated

204.8 °F (96.1 °C) estimated

Solubility

Flash point Boiling point

Specific gravity

None Klown.	
Hazardous decomposition products	May include oxides of nitrogen.
	11. Toxicological Information
Acute effects	Acute LD50: 9198 mg/kg estimated, Rat, Oral Acute LD50: 5699 mg/kg estimated, Rat, Dermal Acute LC50: 51 mg/l/4h estimated, Rat, Inhalation
Sensitization	Not expected to be hazardous by OSHA criteria.
Local effects	Liver toxicity. Blood disorder may occur after ingestion. Components of the product may be absorbed into the body through the skin.
Chronic effects	Hazardous by OSHA criteria. This product may be harmful if it is absorbed through the skin. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Subchronic effects	Kidney injury may occur. Blood disorder may occur after prolonged inhalation. Blood disorder may occur after prolonged skin contact.
Neurological effects	Not expected to be hazardous by OSHA criteria.
Mutagenicity	Not expected to be hazardous by OSHA criteria.
Reproductive effects	Not expected to be hazardous by OSHA criteria. Possible reproductive hazard.
Teratogenicity	Not expected to be hazardous by OSHA criteria.
Epidemiology	Hazardous by OSHA criteria.
Further information	Symptoms may be delayed.

	12. Ecological Information			
Ecotoxicity	LC50 28957 mg/L estimated, Fish, 96.00 Hours, EC50 43419 mg/L estimated, Daphnia, 48.00 Hours, IC50 12207 mg/L estimated, Algae, 72.00 Hours, Components of this product have been identified as having potential environmental concerns.			
	13. Disposal Considerations			
Waste codes	D001: Waste Flammable material with a flash point <140 F			
Disposal instructions	Contents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.			
	14. Transport Information			
Department of Transportation ((DOT) Requirements			
Basic shipping requirement	is:			
Proper shipping name	Consumer commodity			
Hazard class	ORM-D			
Subsidiary hazard class	None			
Additional information:				
Packaging exceptions	156, 306			
Packaging non bulk	156, 306			
Packaging bulk	None			
IMDG				
Basic shipping requirement	ts:			
Proper shipping name	AEROSOLS, flammable			
Hazard class	2.1			
UN number	1950			
Additional information:				
Packaging exceptions	LTD QTY			
Item	5F 2			
Labels required	2.1			
Transport Category	2			
ΙΑΤΑ				
Basic shipping requirement	is:			

Basic shipping requirements:	
Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes chemical

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and F	Reauthorizati	on Act of 1986 (SARA)		
Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No			
Section 302 extremely hazardous substance	No			
Section 311 hazardous chemical	Yes			
Inventory status				
Country(s) or region	Inventory name		On inventory (yes/no)*	
China	Inventory of Existing Chemical Substances in China (IECSC) No			
Europe	European Inventory of New and Existing Chemicals (EINECS) Yes			
Europe	European List of Notified Chemical Substances (ELINCS) No			
Japan	Inventory of Existing and New Chemical Substances (ENCS) No			
Korea	Existing Chemicals List (ECL) No			
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory Yes			
A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)				
State regulations				
U.S Pennsylvania - RTK (Right to Know) List				
2-Butoxyethanol	111-76-2	Present		
Ethyl Alcohol	64-17-5	Present		
n-Butane Propane	106-97-8 74-98-6	Present Present		
16. Other Information				
HMIS® ratings	Health: 1* Flammability: 1 Physical hazard: 0			
Prepared by	-	Regulatory Compliance		
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such			

material used in combination with any other materials or in any process, unless specified

Issue date

in the text.

20-Jul-2007